BANGLADESH - Rohingya Refugee Crisis - Cox's Bazar District - Camp 20: Flood Exposure - Shelters INTER SECTOR COORDINATION GROUP VERSION 1.0
For Humanitarian Purposes Only Flood Hazard - Hydrodynamic Modelling **Shelters Exposed to Floods** Number of Shelters Exposed to Floods per 50m Grid Production date: 29.03.2021 Camp 17 Camp 20 Camp 20 Camp 20 Camp 18 Camp 18 Camp 19

Flood Depth

Low (0.05 to 0.5m)

Moderate (0.5 to 1m)

High (> 1m)
Camp 20

Roads

Block Boundary

Flood Damage to Shelters

Camp 20

Roads

Block Boundary

Fully Damaged (> 1m)

Partially Damaged (0.1 to 1m)

Description:

This map shows modelled water depths from a 10-year average return interval. This map is designed to assist planners and decision makers identify priority areas for Background: Hillshade derived from NPM - UAV Orthographic DEM, January 2019

uncertainty. The areas outside the flood zones are not necessarily free from any danger.

Flood depths are derived from hydrodynamic flood modelling (Deltares & WFP, Further details on the modelling can be found in the Summary Report produced by 2019). They can be seen in full in the Flood Hazard – Hydrodynamic Modelling – 10 the Natural Hazards and Risk Analysis Task Force in 2019. Please submit any requests to the ISCG Information Management Unit

planning decisions. Map results need to be ground verified and decisions combined with Structure Footprint: UNOSAT-REACH, 2019

data and computational modelling; they are not ground proofed and are inherently limited by
the quality of the input data and/or model assumptions and therefore hold a degree of
Coordinate System: WGS 1984 UTM Zone 46N

specific on-site evaluation and appropriate technical expertise. The map does not provide Hydrodynamic Modelling: Deltares, 2019

any information about the flow speeds or directions. Results are derived from remote sensing Camp Boundary: ISCG, 2020

(ARI) pluvial flood event from 24hrs of sustained precipitation. Maps also indicate interventions at camp level. It is NOT designed as a stand-alone tool for detailed site Drone Imagery: IOM NPM, January 2019

requests to the ISCG Information Management Unit.

the maximum flood depths within structures.

0.05 to 0.5m: low flood depth and partial damage.

0.5 to 1.0m: moderate flood depth and full damage.

1.0m or higher: high flood depth and full damage.

Year Average Return Interval v2.1 map (REACH, 2019).

Depth Classification

Camp 20

Block Boundary